



TECHNICAL DATA SHEET

Quality: EVA FOAM | CEVA125

Properties

- Available in Black.
- Size Specification : 1000mm*1000mm or 1000mm*2000mm

Technical Specifications

Physical Property	Data	Test Regulation
Cell structure	Closed cell	
Density	150 ± 15	
Hardness (Shore A)	20±5°	DIN 53505
Compression Hardness 25% Deformation	80 ±15 kPa	ISO 6916
Compression Hardness 50% Deformation	180 ±15 kPa	ISO 6916
Elongation at break	>210%	
Tensile Strengt	1,2 N/mm ²	
DVR (24h/70°/50%)	51,40%	(Do-D2)/Do
Permanent Deformation (24h/70°/50%)	102,8%	(Do-D2)/(Do-D1)
DVR (72h/RT/50%)	35,5%	
Permanent Deformation (72h/RT/50%)	71%	
Special Feature	Sulfur Free	

The above information has been determined as a result of tests carried out in laboratory environment, but it is the user's responsibility to determine the suitability for usage. Cetlas Kaucuk ve Plastik San. Tic. Ltd. Sti. cannot guarantee for suitability of the products, due to it does not know the conditions of usage that will expose to which these products will be exposed. Cetlas Kaucuk ve Plastik San. Tic. Ltd. Sti. reserves the right to change the specifications of its products without notice.

CETLAS KAUCUK VE PLASTIK SAN. TIC. LTD. STI.

Akcaburgaz Mah. 137 Sok. No:11-11/A 34522 Esenyurt – Istanbul - TURKIYE

