



TECHNICAL DATA SHEET

Quality: EVA FOAM | CEVA250

Properties

- Available in Blue.
- Size Specification : 1000mm*1000mm or 1000mm*2000mm

Technical Specifications

Physical Property	Data	Test Regulation
Cell structure	Closed cell	
Density	230 ± 15	
Hardness (Shore A)	30±5°	DIN 53505
Compression Hardness 25% Deformation	190 ±15 kPa	ISO 6916
Compression Hardness 50% Deformation	390 ±15 kPa	ISO 6916
Elongation at break	>260%	
Tensile Strengt	1,6 N/mm ²	
DVR (24h/70°/50%)	52,2%	(Do-D2)/Do
Permanent Deformation (24h/70°/50%)	102,6%	(Do-D2)/(Do-D1)
DVR (72h/RT/50%)	23,5%	
Permanent Deformation (72h/RT/50%)	46,2%	
Special Feature	Sulfur Free	

The above information has been determined as a result of tests carried out in laboratory environment, but it is the user's responsibility to determine the suitability for usage. Cetlas Kaucuk ve Plastik San. Tic. Ltd. Sti. cannot guarantee for suitability of the products, due to it does not know the conditions of usage that will expose to which these products will be exposed. Cetlas Kaucuk ve Plastik San. Tic. Ltd. Sti. reserves the right to change the specifications of its products without notice.

CETLAS KAUCUK VE PLASTIK SAN. TIC. LTD. STI.

Akcaburgaz Mah. 137 Sok. No:11-11/A 34522 Esenyurt – Istanbul - TURKIYE

